



## ELECTRIC HIGH PRESSURE UNIT (21 LPM AT 160 BAR)

€2.750,00

Removes light fouling from hulls, propellers  
and underwater surfaces  
Big cartridge filter at pump inlet  
Motor thermal protection

---

**SKU:** HDE160\_21

**Categories:** [High Pressure Units](#)

**Tags:** [CW200](#), [Economic](#), [Electric](#)

## PRODUCT DESCRIPTION

Electric motor 5.5 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 160 bar (5.5 gpm at 2320 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Connection and control for extern selfpriming pump 220vac / Weight 185kg / Dimensions: 850x540x950mm)

## SPECIFICATIONS

Brand	DiveWise Equipment
Power (kW)	5.5
Power (HP)	7.5
Design pressure (bar)	160
Design pressure (psi)	2320
Flow (LPM)	21
Flow (GPM)	5.5
RPM	1500
Drive	Electric
Dimensions (LxWxH) (mm)	850x540x950
Lenght (mm)	850
Lenght (inch)	33.5
Width (mm)	540
Width (inch)	21.3
Height (mm)	950
Height (inch)	37.4
Weight (kg)	185
Weight (lbs)	407.9
Application	Underwater cleaning of light fouling
Voltage	400VAC 3-phase
Optional	Connection and control for extern selfpriming pump 220vac
CE Certified	Yes
SIR Certified	Optional