



**ELECTRIC HIGH PRESSURE UNIT (21 LPM
AT 160 BAR)**

€2.750,00

Removes light fouling from hulls, propellers
and underwater surfaces
Big cartridge filter at pump inlet
Motor thermal protection

SKU: HDE160_21

Categories: [High Pressure Units](#)

Tags: [CW200](#), [Economic](#), [Electric](#)

PRODUCT DESCRIPTION

Electric motor 5.5 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 160 bar (5.5 gpm at 2320 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Connection and control for extern selfpriming pump 220vac / Weight 185kg / Dimensions: 850x540x950mm)

SPECIFICATIONS

| | |
|-------------------------|---|
| Brand | DiveWise Equipment |
| Power (kW) | 5.5 |
| Power (HP) | 7.5 |
| Design pressure (bar) | 160 |
| Design pressure (psi) | 2320 |
| Flow (LPM) | 21 |
| Flow (GPM) | 5.5 |
| RPM | 1500 |
| Drive | Electric |
| Dimensions (LxWxH) (mm) | 850x540x950 |
| Lenght (mm) | 850 |
| Lenght (inch) | 33.5 |
| Width (mm) | 540 |
| Width (inch) | 21.3 |
| Height (mm) | 950 |
| Height (inch) | 37.4 |
| Weight (kg) | 185 |
| Weight (lbs) | 407.9 |
| Application | Underwater cleaning of light fouling |
| Voltage | 400VAC 3-phase |
| Optional | Connection and control for extern selfpriming pump 220vac |
| CE Certified | Yes |
| SIR Certified | Optional |