



**ELECTRIC HIGH PRESSURE UNIT (21 LPM  
AT 160 BAR)**

**€2.750,00**

Removes light fouling from hulls, propellers  
and underwater surfaces  
Big cartridge filter at pump inlet  
Motor thermal protection

---

**SKU:** HDE160\_21

**Categories:** [High Pressure Units](#)

**Tags:** [CW200](#), [Economic](#), [Electric](#)

**PRODUCT DESCRIPTION**

Electric motor 5.5 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 160 bar (5.5 gpm at 2320 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Connection and control for extern selfpriming pump 220vac / Weight 185kg / Dimensions: 850x540x950mm)

**SPECIFICATIONS**

<b>Brand</b>	DiveWise Equipment
<b>Power (kW)</b>	5.5
<b>Power (HP)</b>	7.5
<b>Design pressure (bar)</b>	160
<b>Design pressure (psi)</b>	2320
<b>Flow (LPM)</b>	21
<b>Flow (GPM)</b>	5.5
<b>RPM</b>	1500
<b>Drive</b>	Electric
<b>Dimensions (LxWxH) (mm)</b>	850x540x950
<b>Lenght (mm)</b>	850
<b>Lenght (inch)</b>	33.5
<b>Width (mm)</b>	540
<b>Width (inch)</b>	21.3
<b>Height (mm)</b>	950
<b>Height (inch)</b>	37.4
<b>Weight (kg)</b>	185
<b>Weight (lbs)</b>	407.9
<b>Application</b>	Underwater cleaning of light fouling
<b>Voltage</b>	400VAC 3-phase
<b>Optional</b>	Connection and control for extern selfpriming pump 220vac
<b>CE Certified</b>	Yes
<b>SIR Certified</b>	Optional