

DIESEL HIGH PRESSURE UNIT (21 LPM AT 200 BAR)

€6.654,00

Removes light fouling from hulls, propellers and underwater surfaces
Big cartridge filter at pump inlet
Motor thermal protection

SKU: HDMD160-21
Categories: High Pressure Units
Tags: CW200, Diesel, Economic

PRODUCT DESCRIPTION

Honda GX390 petrol engine. Four wheel frame with two pneumatic wheels and two castor wheels. Gearbox driven pump at 1560 rpm. Max performance 21 LPM at 200 bar. Strong tubular frame with stainless steel covers. Automatic rpm decelerator for reduced speed in bypass mode. Comet RW Premium pump with three ceramic pistons and brass pump head. Self priming capability for suction from external tank. Self cleaning water suction filter. Low pressure detergent suction with adjustable ejector. Overheating thermostatic valve. Unit weight 72 kg. Dimensions 950 x 680 x 950 mm.

DIVEWISE
EQUIPMENT

SPECIFICATIONS

Brand	DiveWise Equipment
Power (kW)	7,4
Power (HP)	10
Design pressure (bar)	200
Design pressure (psi)	2900
Flow (LPM)	21
Flow (GPM)	5,5
RPM	1560
Drive	Diesel
Dimensions (LxWxH) (mm)	950x680x950
Lenght (mm)	950
Lenght (inch)	37,4
Width (mm)	680
Width (inch)	26,8
Height (mm)	950
Height (inch)	37,4
Weight (kg)	72
Weight (lbs)	231,49
Application	Underwater cleaning of medium fouling
CE Certified	Yes
SIR Certified	Optional