



ECONOMIC CLEANING KIT WITH CW300 CAVITATION GUN AND ELECTRIC HIGH PRESSURE UNIT (15 LPM AT 210 BAR)

Complete set for cavitation cleaning.

Including:

High Pressure gun

Economic Pump

50 meter Neutrally Buoyant hose

Supply pump

SKU: HDE210_15, CW300T1, DE148-06-HS24M-HM24M-50000, EWSP230

Categories: [Cleaning kit](#)

Tags: [Cleaning kit](#), [Economic](#)

PRODUCT DESCRIPTION

Economic cavitation cleaning kit for removing light and medium fouling, including:

CW300T1 Long Cavitation Cleaning gun (Max. 28 LPM at 300 bar)

Ergonomic handgun / Handle with safety latch / Swiveling Hose inlet connection / Stainless steel lance protection / Tapered lance end with red marking / Max. recommended working pressure 300 bar (4350 psi) / Maximum flow 28 LPM (7.5 gpm) / Safety ring shield on lance around nozzle / CE certified / SIR certified / Not according IMCA guidelines / Lance length 668mm / Weight 1600 gram (under water 800 gram) / Optional adjustable lance handle

HDE210_15 Electric High Pressure Unit (15 LPM at 210 bar)

Electric motor 5,5 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 15 LPM at 210 bar (4 gpm at 3045 psi) / CE certified / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Connection and control for extern selfpriming pump 220vac / Weight 185kg / Dimensions: 850x540x950mm)

DE148-06-HS24M-HM24M-50000 3 /8" Neutrally Buoyant High Pressure Hose (W.P. 250 bar) - 50 mtr
3 /8" Neutrally Buoyant High Pressure Hose (W.P. 250 bar) / 50 mtr / Quick-connect couplings /
Recommended for ROV cavitation cleaning

EWSP230 Electric water supply pump 230V

Electric water supply pump 230VAC with 10 meter 1" hose / quick-connect couplings / 270W /
270mm x 200mm x 435mm / 15.8 kg

SPECIFICATIONS