



## ELECTRIC HIGH PRESSURE PRO CART WITH WATERCOOLED FREQUENCY INVERTER 22KW | 300 BAR/31 LPM

€23.629,00

Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 22 | Power (HP) 29,9 | Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 31 | (GPM) 8,2 | Engine / Motor Nicolini | Type pump CH 31/300

---

**SKU:** HDE22-300-31CH-PRO

**Categories:** [High Pressure Units](#)

**Tags:** [Electric](#), [PRO Cart](#)

## PRODUCT DESCRIPTION

Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 22 | Power (HP) 29,9 | Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 31 | (GPM) 8,2 | Engine / Motor Nicolini | Type pump CH 31/300

## SPECIFICATIONS

|                           |                    |
|---------------------------|--------------------|
| Type pump                 | CH 31/300          |
| Dimensions (LxWxH) (inch) | 47,2×29,5×35,4     |
| Brand                     | DiveWise Equipment |
| Power (kW)                | 22                 |
| Power (HP)                | 29,9               |
| Design pressure (bar)     | 300                |
| Design pressure (psi)     | 4350               |
| Flow pump (LPM)           | 31                 |
| Flow pump (GPM)           | 8,2                |
| Flow (LPM)                | 31                 |
| Flow (GPM)                | 8,2                |
| RPM                       | 1450               |
| Engine/motor power        | 22                 |
| Drive                     | Electric           |
| Engine / Motor            | Nicolini           |
| Direction of rotation     | CW                 |
| RPM shaft                 | 1450               |
| Gear ratio                | 1                  |
| Pump speed                | 1450               |
| Dimensions (LxWxH) (mm)   | 1200x750x900       |
| Lenght (mm)               | 1200               |
| Lenght (inch)             | 47.3               |
| Width (mm)                | 750                |
| Width (inch)              | 29,6               |
| Height (mm)               | 900                |
| Height (inch)             | 35.5               |

|                     |                                                          |
|---------------------|----------------------------------------------------------|
| <b>Weight (kg)</b>  | 280                                                      |
| <b>Weight (lbs)</b> | 617,4                                                    |
| <b>Application</b>  | Drilling, Grinding, Underwater cleaning of heavy fouling |
| <b>Voltage</b>      | 3-phase 400VAC / 50 Hz (optional 440VAC / 60 Hz)         |