



**ELECTRIC HIGH PRESSURE PRO CART
WITH WATERCOOLED FREQUENCY
INVERTER 30KW | 300 BAR/43 LPM**

€23.629,00

Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30 | Power (HP) 40,8 | Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 43 | (GPM) 11,4 | Engine / Motor Nicolini | Type pump PRO-T22

SKU: HDE30-300-43-PRO

Categories: [High Pressure Units](#)

Tags: [Electric](#), [PRO Cart](#)

PRODUCT DESCRIPTION

Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30 | Power (HP) 40,8 | Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 43 | (GPM) 11,4 | Engine / Motor Nicolini | Type pump PRO-T22 | Max. Amperage 58A | Voltage 380~415 VAC at 50Hz and 380~430 VAC at 60 Hz | Phase connection 3-phase | Required power connector 3P + N + E | Required water supply 50 LPM at 1,5 bar

SPECIFICATIONS

Type pump	PRO-T22
Dimensions (LxWxH) (inch)	47,2×29,5×35,4
Brand	DiveWise Equipment
Power (kW)	30
Power (HP)	40,8
Design pressure (bar)	300
Design pressure (psi)	4350
Flow pump (LPM)	43
Flow pump (GPM)	11,4
Flow (LPM)	43
Flow (GPM)	11,4
RPM	1450
Engine/motor power	30
Drive	Electric
Engine / Motor	Nicolini
Direction of rotation	CW
RPM shaft	1450
Gear ratio	1
Pump speed	1450
Dimensions (LxWxH) (mm)	1200x750x900
Lenght (mm)	1200
Lenght (inch)	47.3
Width (mm)	750
Width (inch)	29,6
Height (mm)	900
Height (inch)	35.5

Weight (kg)	325
Weight (lbs)	716,6
Application	Drilling, Grinding, Underwater cleaning of heavy fouling
Voltage	3-phase 400VAC / 50 Hz (optional 440VAC / 60 Hz)