



**ELECTRIC HIGH PRESSURE UNIT (15 LPM  
AT 210 BAR)**

**€2.150,00**

Removes light fouling from hulls, propellers  
and underwater surfaces  
Big cartridge filter at pump inlet  
Motor thermal protection

---

**SKU:** HDE210\_15

**Categories:** [High Pressure Units](#)

**Tags:** [CW200](#), [Economic](#), [Electric](#)

**PRODUCT DESCRIPTION**

Electric motor 5.5 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 15 LPM at 210 bar (4 gpm at 3045 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification (optional) / Connection and control for extern selfpriming pump 220vac / Weight 185kg / Dimensions: 850x540x950mm)

## SPECIFICATIONS

|                         |                                                           |
|-------------------------|-----------------------------------------------------------|
| Brand                   | DiveWise Equipment                                        |
| Power (kW)              | 5.5                                                       |
| Power (HP)              | 7.5                                                       |
| Design pressure (bar)   | 210                                                       |
| Design pressure (psi)   | 3045                                                      |
| Flow (LPM)              | 15                                                        |
| Flow (GPM)              | 4                                                         |
| RPM                     | 1500                                                      |
| Drive                   | Electric                                                  |
| Dimensions (LxWxH) (mm) | 850x540x950                                               |
| Lenght (mm)             | 850                                                       |
| Lenght (inch)           | 33.5                                                      |
| Width (mm)              | 540                                                       |
| Width (inch)            | 21.3                                                      |
| Height (mm)             | 950                                                       |
| Height (inch)           | 37.4                                                      |
| Weight (kg)             | 185                                                       |
| Weight (lbs)            | 407.9                                                     |
| Application             | Underwater cleaning of light fouling                      |
| Voltage                 | 400VAC 3-phase                                            |
| Optional                | Connection and control for extern selfpriming pump 220vac |
| CE Certified            | Yes                                                       |
| SIR Certified           | Optional                                                  |