



ELECTRIC HIGH PRESSURE UNIT (21 LPM AT 160 BAR)

€2.750,00

Removes light fouling from hulls, propellers and underwater surfaces
Big cartridge filter at pump inlet
Motor thermal protection

SKU: HDE160 21

Categories: <u>High Pressure Units</u>
Tags: <u>CW200</u>, <u>Economic</u>, <u>Electric</u>

PRODUCT DESCRIPTION

Electric motor 5.5 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 160 bar (5.5 gpm at 2320 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergeny-stop remote for SIR certification (optional) / Connection and control for extern selfpriming pump 220vac / Weight 185kg / Dimensions: 850x540x950mm)



SPECIFICATIONS

Brand DiveWise Equipment

Power (kW) 5.5

Power (HP) 7.5

Design pressure (bar) 160

Design pressure (psi) 2320

Flow (LPM) 21

Flow (GPM) 5,5

RPM 1500

Drive Electric

Dimensions (LxWxH) (mm) 850x540x950

Lenght (mm) 850

Lenght (inch) 33,5

Width (mm) 540

Width (inch) 21,3

Height (mm) 950

Height (inch) 37.4

Weight (kg) 185

Weight (lbs) 407,9

Application Underwater cleaning of light fouling

Voltage 400VAC 3-phase

Optional Connection and control for extern selfpriming pump 220vac

CE Certified Yes

SIR Certified Optional