

ELECTRIC HIGH PRESSURE UNIT (21 LPM AT 250 BAR)

€4.950,00

Removes light fouling from hulls, propellers and underwater surfaces
Big cartridge filter at pump inlet
Motor thermal protection

SKU: HDE250_21
Categories: High Pressure Units
Tags: CW300, Economic, Electric

PRODUCT DESCRIPTION

Electric motor 8,8 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. pressure 21 LPM at 250 bar (5,5 gpm at 3625 psi) / / Direct driven pump / Overheating thermostatic valve / Hour counter / Remote switch and motor cut-out with thermal relay / Emergency stop button / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergeny-stop remote for SIR certification (optional) / Weight 161kg) / Dimensions: 900x750x950mm

DIVEWISE
EQUIPMENT

SPECIFICATIONS

Brand	DiveWise Equipment
Power (kW)	8,8
Power (HP)	12
Design pressure (bar)	250
Design pressure (psi)	3625
Flow (LPM)	21
Flow (GPM)	5,5
RPM	1500
Drive	Electric
Dimensions (LxWxH) (mm)	900x750x950
Lenght (mm)	900
Lenght (inch)	35,5
Width (mm)	750
Width (inch)	29,6
Height (mm)	950
Height (inch)	37,4
Weight (kg)	161
Weight (lbs)	355
Application	Drilling, Grinding, Underwater cleaning of medium fouling
Voltage	400VAC 3-phase
CE Certified	Yes
SIR Certified	Optional