OFFSHORE PRO KIT WITH CW350 CAVITATION GUN AND ELECTRIC HIGH PRESSURE UNIT (43 LPM AT 300 BAR)

Complete set Offshore PRO cavitation cleaning kit for removing medium to hard fouling, including:
High Pressure gun
Offshore PRO Pump
50 meter Neutrally buoyant hose
Supply pump

SKU: HDE30-300-43-PRO, CW350T1, DE149-08-HS24M-HM24M-50000, EWSP230-1
Categories: Cleaning kit
Tags: Cleaning kit, Offshore PRO

PRODUCT DESCRIPTION

Offshore PRO cavitation cleaning kit for removing medium to hard fouling, including:

CW350T1 Zero-Thrust Long Cavitation Cleaning gun (Max. 40 LPM at 300 bar)
Ergonomic handgun / Handle with safety latch / Swiveling hose inlet connection / Stainless steel lance protection / Tapered lance end with red marking / Max. recommended working pressure 300 bar (4350 psi) / Maximum flow 40 LPM (10,5 gpm) / Safety ring shield on lance around nozzle / CE certified / SIR certified / According to IMCA guidelines / Lance length 668mm / Retro lance length 700mm / Weight 2300 gram (under water 1200 gram) / Optional adjustable lance handle

HDE30-300-43-PRO Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30
Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30 | Power (HP) 40,8| Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 43 | (GPM) 11,4 | Engine / Motor Nicolini | Type pump PRO-T22

DIVEWISE
EQUIPMENT

DE149-08-HS24M-HM24M-50000 1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) - 50 mtr
1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) / 50 mtr / Quick-connect couplings / Recommended for ROV cavitation cleaning

EWSP230Electric submersible water supply pump set 230V
Electric water supply pump 230VAC with 10 meter 1 1/4" inch hose- GK-GK / quick-connect couplings / 270W / 270mm x 200mm x 435mm / 15.8 kg / Maximum high pressure unit flow rate: 30 L/min / Maximum pumping height: 4 m

SPECIFICATIONS