OFFSHORE PRO KIT WITH GR200 GRINDER AND ELECTRIC HIGH PRESSURE UNIT (43 LPM AT 300 BAR)

Complete set Offshore PRO cavitation cleaning kit for removing medium to hard fouling, including:
Underwater Tool
Offshore PRO Pump
2 x 20 meter Rubber hose
Supply pump

SKU: HDE30-300-43-PRO, GR200T1, DE522-08-HS24M-HM24M-20000, EWSP230-1
Categories: Grinding kit
Tags: Grinding kit, Offshore PRO

PRODUCT DESCRIPTION

Offshore PRO cavitation cleaning kit for removing medium to hard fouling, including:

GR200T1 Waterhydraulic Underwater Grinder
Including:
- ToolHose 2m 1/4" (2x)
- Storage Case
- Maintenance Tool
- 125mm - 180mm discs (5" - 7")

Rugged grinder tool / Handle with safety latch / Swiveling hose inlet connection / Water hydraulic driven / Grinding disc hand protection / Max. working pressure 30 LPM at 300 bar / Max. 15,000 rpm / Max. 3kW / M14x2 thread disc connection / Compatible cutting blades: 5" (125mm) or optional 7" (180mm) / Weight 2000 gram (under water 1500 gram) / corrosion resistant materials / CE certified / SIR certified

HDE30-300-43-PRO Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30
Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30 | Power (HP) 40,8| Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 43 | (GPM) 11,4 | Engine / Motor Nicolini | Type pump PRO-T22

DE522-08-HS24M-HM24M-20000 1 /2" Rubber High Pressure Hose (W.P. 440 bar) - 20 mtr (2x)
1 /2" Rubber High Pressure Hose (W.P. 440 bar) / 20 mtr / Quick-connect couplings / Recommended for underwater Tools

EWSP230Electric submersible water supply pump set 230V
Electric water supply pump 230VAC with 10 meter 1 1/4" inch hose- GK-GK / quick-connect couplings / 270W / 270mm x 200mm x 435mm / 15.8 kg / Maximum high pressure unit flow rate: 30 L/min / Maximum pumping height: 4 m

SPECIFICATIONS