

OFFSHORE PRO KIT WITH SR550 CAVITATION CLEANER AND ELECTRIC HIGH PRESSURE UNIT (43 LPM AT 300 BAR)

Complete set Offshore PRO cavitation cleaning kit for removing medium to hard fouling,
including:
Rotor cleaner
Offshore PRO Pump
50 meter Neutrally buoyant hose
Supply pump

SKU: HDE30-300-43-PRO, SR550T1, DE149-08-HS24M-HM24M-50000, EWSP230-1
Categories: Cleaning kit
Tags: Cleaning kit, Offshore PRO

PRODUCT DESCRIPTION

Offshore PRO cavitation cleaning kit for removing medium to hard fouling, including:

SR550T1 Cavitation Cleaning Surface Rotor Cleaner 550mm
Round plastic dome 550mm / Remote handle with safety latch / Swiveling hose inlet connection / 2" camlock hose connection / with high pressure water injector inlet on 2" connection / Max. working pressure 40 LPM at 300 bar / 2 handgrips / 3 castors / corrosion resistant materials / CE certified

HDE30-300-43-PRO Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30
Electric High Pressure Pro Cart with watercooled frequency inverter Power (kW) 30 | Power (HP) 40,8| Pressure (bar) 300 | Pressure (psi) 4350 | Flow pump (LPM) 43 | (GPM) 11,4 | Engine / Motor Nicolini | Type pump PRO-T22

DE149-08-HS24M-HM24M-50000 1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) - 50 mtr

1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) / 50 mtr / Quick-connect couplings / Recommended for ROV cavitation cleaning

EWSP230 Electric submersible water supply pump set 230V
Electric water supply pump 230VAC with 10 meter 1 1/4" inch hose- GK-GK / quick-connect couplings / 270W / 270mm x 200mm x 435mm / 15.8 kg / Maximum high pressure unit flow rate: 30 L/min / Maximum pumping height: 4 m

SPECIFICATIONS