

PETROL HIGH PRESSURE UNIT (30 LPM AT 280 BAR)

€9.150,00

Big cartridge filter at pump inlet
Adjustable pressure valve
Electric start, thermal protection and hour counter

SKU: HDMP280_30
Categories: High Pressure Units
Tags: CW250, CW300, CW350, DR200, GR200, Petrol, Semi PRO, SR450

PRODUCT DESCRIPTION

Engine Mo33,5Petrol driven, 2 cilinder Aircooled Honda GX690 / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. 30 LPM at 280 bar (7,9 gpm at 4060 psi) / / Gearbox driven pump / Electrical starting / No engine-oil safety device (oil-alert) / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergeny-stop remote for SIR certification / Weight 150kg / Dimensions 1000x820x850mm

DIVEWISE
EQUIPMENT

SPECIFICATIONS

Brand	DiveWise Equipment
Design pressure (bar)	280
Design pressure (psi)	4060
Flow (LPM)	30
Flow (GPM)	7,9
RPM	1500
Drive	Petrol
Engine / Motor	2 cilinder Aircooled Honda GX690
Lenght (mm)	1000
Lenght (inch)	39,4
Width (mm)	820
Width (inch)	32,3
Height (mm)	850
Height (inch)	33,5
Weight (kg)	150
Weight (lbs)	330,8
Application	Drilling, Grinding, Underwater cleaning of heavy fouling
CE Certified	Yes
SIR Certified	Optional