

SEMI PRO CLEANING KIT WITH CW350 CAVITATION GUN AND ELECTRIC HIGH PRESSURE UNIT (33 LPM AT 250 BAR)

Complete set for cavitation cleaning.
Including:
High Pressure gun
Semi PRO Pump
50 meter Neutrally Buoyant hose
Supply pump

SKU: HDE250_33, CW350T1, DE149-08-HS24M-HM24M-50000, EWSP230
Categories: Cleaning kit
Tags: Cleaning kit, Semi PRO

PRODUCT DESCRIPTION

Semi PRO cavitation cleaning kit for removing medium to hard fouling, including:

CW350T1 Zero-Thrust Long Cavitation Cleaning gun (Max. 40 LPM at 300 bar)
Ergonomic handgun / Handle with safety latch / Swiveling hose inlet connection / Stainless steel lance protection / Tapered lance end with red marking / Max. recommended working pressure 300 bar (4350 psi) / Maximum flow 40 LPM (10,5 gpm) / Safety ring shield on lance around nozzle / CE certified / SIR certified / According to IMCA guidelines / Lance length 668mm / Retro lance length 700mm / Weight 2300 gram (under water 1200 gram) / Optional adjustable lance handle

HDE250_33 Electric High Pressure Unit (33 LPM at 250 bar)
Electric motor 14,7 Kw / 400VAC 3-phase / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. 33 LPM at 300bar (8,7 gpm at 3625 psi) / CE certified / Direct driven pump / Overheating thermostatic valve / Hour counter / Emergency stop button / Remote switch and motor cut-out with thermal relay / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergeny-stop remote for SIR certification (optional) / Weight 175kg / Dimensions 1000x750x850mm

DE149-08-HS24M-HM24M-50000 1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) - 50 mtr
1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) / 50 mtr / Quick-connect couplings / Recommended for ROV cavitation cleaning

EWSP230 Electric submersible water supply pump set 230V
Electric water supply pump 230VAC with 10 meter 1 1/4" inch hose- GK-GK / quick-connect couplings / 270W / 270mm x 200mm x 435mm / 15.8 kg / Maximum high pressure unit flow rate: 30 L/min / Maximum pumping height: 4 m

SPECIFICATIONS