

SEMI PRO KIT WITH GR200 GRINDER AND DIESEL HIGH PRESSURE UNIT (30 LPM AT 280 BAR)

Complete set for cavitation cleaning.
Including:
Underwater Tool
Semi PRO Pump
2 x 20 meter Rubber hose
Supply pump

SKU: HDMD280_30, GR200T1, DE522-08-HS24M-HM24M-20000, EWSP230
Categories: Grinding kit
Tags: Diesel, Grinding kit, Semi PRO

PRODUCT DESCRIPTION

Semi PRO cavitation cleaning kit for removing medium to hard fouling, including:

GR200T1 Waterhydraulic Underwater Grinder
Including:
- ToolHose 2m 1/4" (2x)
- Storage Case
- Maintenance Tool
- 125mm - 180mm discs (5" - 7")

Rugged grinder tool / Handle with safety latch / Swiveling hose inlet connection / Water hydraulic driven / Grinding disc hand protection / Max. working pressure 30 LPM at 300 bar / Max. 15,000 rpm / Max. 3kW / M14x2 thread disc connection / Compatible cutting blades: 5" (125mm) or optional 7" (180mm) / Weight 2000 gram (under water 1500 gram) / corrosion resistant materials / CE certified / SIR certified

HDMD280_30 Diesel High Pressure Unit (30 LPM at 280 bar)
Diesel driven, 2 cilinder Aircooled KohlerKDW1003 / 4 wheels with air tyres / Max. 1500 rpm / Strong,

lightweight frame / Max. pressure 30 LPM at 280 bar (7,9 gpm at 4060 psi) / CE certified / Gearbox driven pump / Electrical starting / Automatic decelerator to reduce the number of revs in the bypass phase / No engine-oil safety device (oil-alert) / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergeny-stop remote for SIR certification (optional) / Weight 285kg) / Dimensions 1370x850x1020mm

DE522-08-HS24M-HM24M-20000 1 /2" Rubber High Pressure Hose (W.P. 440 bar) - 20 mtr (2x)
1 /2" Rubber High Pressure Hose (W.P. 440 bar) / 20 mtr / Quick-connect couplings / Recommended for underwater Tools

EWSP230 Electric water supply pump 230V
Electric water supply pump 230VAC with 10 meter 1" hose / quick-connect couplings / 270W / 270mm x 200mm x 435mm / 15.8 kg

SPECIFICATIONS