



**SEMI PRO KIT WITH GR200 GRINDER AND  
PETROL HIGH PRESSURE UNIT (30 LPM AT  
280 BAR)**

Complete set for cavitation cleaning.  
Including:  
Underwater Tool  
Semi PRO Pump  
2 x 20 meter Rubber hose  
Supply pump

---

**SKU:** HDMP280\_30, GR200T1, DE522-08-  
HS24M-HM24M-20000, EWSP230

**Categories:** [Grinding kit](#)

**Tags:** [Grinding kit](#), [Semi PRO](#)

## PRODUCT DESCRIPTION

Semi PRO cavitation cleaning kit for removing medium to hard fouling, including:

GR200T1 Waterhydraulic Underwater Grinder

Including:

- ToolHose 2m 1/4" (2x)
- Storage Case
- Maintenance Tool
- 125mm - 180mm discs (5" - 7")

Rugged grinder tool / Handle with safety latch / Swiveling hose inlet connection / Water hydraulic driven / Grinding disc hand protection / Max. working pressure 30 LPM at 300 bar / Max. 15,000 rpm / Max. 3kW / M14x2 thread disc connection / Compatible cutting blades: 5" (125mm) or optional 7" (180mm) / Weight 2000 gram (under water 1500 gram) / corrosion resistant materials / CE certified / SIR certified

HDMP280\_30 Petrol High Pressure Unit (30 LPM at 280 bar)

Petrol driven, 2 cilinder Aircooled Honda GX690 / 4 wheels with air tyres / Max. 1500 rpm / Strong,

lightweight frame / Max. 30 LPM at 280 bar (7,9 gpm at 4060 psi) / CE certified / Gearbox driven pump / Electrical starting / No engine-oil safety device (oil-alert) / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergency-stop remote for SIR certification / Weight 150kg / Dimensions 1000x820x850mm

DE522-08-HS24M-HM24M-20000 1 / 2" Rubber High Pressure Hose (W.P. 440 bar) - 20 mtr (2x)  
1 / 2" Rubber High Pressure Hose (W.P. 440 bar) / 20 mtr / Quick-connect couplings / Recommended for underwater Tools

EWSP230 Electric water supply pump 230V

Electric water supply pump 230VAC with 10 meter 1" hose / quick-connect couplings / 270W / 270mm x 200mm x 435mm / 15.8 kg

**SPECIFICATIONS**