

SEMI PRO KIT WITH SR550 CAVITATION ROTOR CLEANER AND PETROL HIGH PRESSURE UNIT (30 LPM AT 280 BAR)

Complete set for cavitation cleaning.
Including:
Rotor cleaner
Semi PRO Pump
50 meter Neutrally Buoyant hose
Supply pump

SKU: HDMP280_30, SR550T1, DE149-08-HS24M-HM24M-50000, EWSP230
Categories: Cleaning kit
Tags: Cleaning kit, Semi PRO

PRODUCT DESCRIPTION

Semi PRO cavitation cleaning kit for removing medium to hard fouling, including:

SR550T1 Cavitation Cleaning Surface Rotor Cleaner 550mm
Round plastic dome 550mm / Remote handle with safety latch / Swiveling hose inlet connection / 2" camlock hose connection / with high pressure water injector inlet on 2" connection / Max. working pressure 40 LPM at 300 bar / 2 handgrips / 3 castors / corrosion resistant materials / CE certified

HDMP280_30 Petrol High Pressure Unit (30 LPM at 280 bar)
Petrol driven, 2 cilinder Aircooled Honda GX690 / 4 wheels with air tyres / Max. 1500 rpm / Strong, lightweight frame / Max. 30 LPM at 280 bar (7,9 gpm at 4060 psi) / CE certified / Gearbox driven pump / Electrical starting / No engine-oil safety device (oil-alert) / Big water filter at pump inlet, readily serviceable cartridge type / Pressure release valve for dry shutoff gun / Zero hose pressure regulator and emergeny-stop remote for SIR certification / Weight 150kg / Dimensions 1000x820x850mm

DE149-08-HS24M-HM24M-50000 1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) - 50 mtr
1 /2" Neutrally Buoyant High Pressure Hose (W.P. 390 bar) / 50 mtr / Quick-connect couplings /

Recommended for ROV cavitation cleaning

EWSP230 Electric submersible water supply pump set 230V
Electric water supply pump 230VAC with 10 meter 1 1/4" inch hose- GK-GK / quick-connect couplings / 270W / 270mm x 200mm x 435mm / 15.8 kg / Maximum high pressure unit flow rate: 30 L/min / Maximum pumping height: 4 m

SPECIFICATIONS